

PORTLAND CEMENT

PRODUCT DATA SHEET



**SOUTHERN
HERITAGE
MASONRY**

PRODUCT DESCRIPTION

Type I portland cement.

Basic Uses

Southern Heritage Masonry Portland Cement is used in a multitude of projects including both residential and commercial construction.

Type I

General purpose cement suitable for all uses where the special properties of other types of portland cement are not required.

Type IA

General purpose cement with an interground air-entraining additive to provide workability in certain applications and to promote durability to freezing and thawing conditions. (Not available at this time)

Type II

General purpose cement typically used in concrete exposed to moderately aggressive sulfate environments. (Not available at this time)

Type II (MH)

General purpose cement used for both moderate heat of hydration and moderate sulfate resistance. (Not available at this time)

Type III

Cement that develops higher strength at early ages when compared with a Type I cement. It is typically used in precast or prestressed concrete, where early strength gain and quick form turnaround are desired. (Not available at this time)

Type V

Cement typically used in concrete exposed to sulfate environments classified as severe and very severe. (Not available at this time)

Applicable Standards

The following standards apply to the use of Southern Heritage Masonry portland cement:

AASHTO M85, *Standard Specification for Portland Cement*

ASTM C150, *Standard Specification for Portland Cement*

Precautions

Freshly mixed cement, mortar, grout or concrete may cause minor skin irritations. Avoid direct contact with skin and eyes and if contacted, wash exposed areas promptly with water. Refer to the applicable Southern Heritage Masonry product SDS prior to use which may be obtained by calling (404) 696-9930.

Availability

Southern Heritage Masonry portland cement is available in 94 lb. bags (42.6 kg) and can be ordered by contacting Southern Heritage Masonry Sales at (404) 696-9930.

WARRANTY

Southern Heritage Masonry warrants that the products identified are in accordance with the appropriate current ASTM and Federal Specifications. No one is authorized to make any modifications or addition to this warranty. Southern Heritage Masonry makes no warranty or representation, either expressed or implied with respect to this product and disclaims any implied warranty of merchantability or fitness for a particular purpose.

As Southern Heritage Masonry has no control over other ingredients mixed with this product or the final application, Southern Heritage Masonry does not and cannot warrant the finished work.

In no event shall Southern Heritage Masonry be liable for direct, indirect, special, incidental or consequential damages arising out of the use of this product, even if advised of the possibility of such damages. In no case shall Southern Heritage Masonry's liability exceed the purchase price of this product.

TECHNICAL SERVICES

Southern Heritage Masonry personnel are available to provide technical assistance by contacting (404) 696-9930

Southern Heritage Masonry LLC
4530 Patton Dr SW # H, Atlanta, GA 30336
(404) 696-9930

WWW.SOUTHERNHERITAGEMASONRY.COM